



## SAVE NOW ON SMB FIREWALLS

Get ready to take your SMB security to the next level with our exclusive SMB Firewalls Sale! For a limited time only, Check Point is offering aggressive discounts on Quantum Spark firewalls using single sku bundles that include the firewall, one, three or five-year services and support options!

> Don't miss out on these incredible deals. Contact your Check Point TD Synnex team at checkpointBD@tdsynnex.com today!


The Quantum Spark 1500 Pro next generation firewalls for small and medium businesses are the industry's first firewalls with integrated AI, ML security and cutting-edge Wi-Fi 6, SD-**Wan, and 5G** cellular. With a best threat prevention up to 2.6 Gbps, always up to date cyberattack protection with a 99.7% catch rate of malware, phishing and ransomware – you are secured!

The Check Point Quantum Spark 1500 Pro security gateway family delivers enterprise-grade security in a series of simple and affordable, all-in-one security solution to protect small business employees, networks, and data from cyber theft.

Models with Wi-Fi and with an embedded 5G modem fit seamlessly into your home and branch office networks. With a zero-touch installation in less than 60 seconds the Spark gateways provide protection not only against phishing and ransomware attacks but also include:

- Next Generation Firewall
- IPSec VPN & SSL-VPN
- Application Control & Web Filtering
- Intrusion Prevention
- Antivirus
- Anti-Bot
- Anti-Spam
- SandBlast Threat Emulation









Quantum Spark 1500 Pro line

The Quantum Spark gateways can be easily managed with an intuitive user-friendly unified management dashboard or a mobile management app.

The management dashboard is designed to increase scalability, improve operational efficiency, and reduce the overall cost for every business. With Zero Touch deployment and pre-defined security policies, your business is secured!

## Popular Bundle skus:

CPAP-SG1535-SNBT-SS-PREM-1Y

CPAP-SG1535-SNBT-SS-PREM-3Y

CPAP-SG1535W-US-SNBT-SS-PREM-5Y

CPAP-SG1555-SNBT-SS-PREM-3Y

CPAP-SG1555W-US-SNBT-SS-PREM-3Y

CPAP-SG1575-SNBT-SS-PREM-1Y


CPAP-SG1575W-US-SNBT-SS-PREM-3Y

CPAP-SG1575-SNBT-SS-PREM-5Y

CPAP-SG1595-SNBT-SS-PREM-1Y

CPAP-SG1595W-US-SNBT-SS-PREM-3Y

CPAP-SG1595-SNBT-SS-PREM-5Y





# SAVE NOW ON SMB FIREWALLS



### **SPECIFICATIONS**

#### 1535, 1555 Pro (Wi-Fi model)

- 1 802.11 a/b/g/n/ac/ax Wi-Fi (option)
- USB port
- 3 5x 1GbE LAN switch
- 4 1x 1GbE WAN interface
- 6 Power button
- 6 USB-C Console port
- 12V power connector






	1535	1555
Enterprise Testing Conditions		
Threat Prevention with Smart Accel*	440 Mbps	585 Mbps
Threat Prevention <sup>1</sup>	340 Mbps	450 Mbps
Next Generation Firewall <sup>2</sup>	600 Mbps	800 Mbps
IPS Throughput	670 Mbps	900 Mbps
Firewall Throughput	1,000 Mbps	1,000 Mbps
2647, 1242 Performance (LAB)		
Firewall 1518 Byte UDP Packets	2,000 Mbps	2,000 Mbps
VPN AES-128 Throughput	970 Mbps	1,300 Mbps
Connections per Second	10,500	14,000
Concurrent Connections	1,000,000	1,000,000
Software		
Security	Firewall, VPN, User Aware, QoS, Application Control, URLF, IPS, Anti-Bot, Antivirus, Anti-Spam, sandboxing	
Unicast, Multicast Routing and Clustering	OSPFv2, BGPv4 and 4++, RIP, PIM (SM, DM, SSM), IGMP, ClusterXL High Availability	
IPv6	local network and internet connections, dual stack tunneling IPv4 over IPv6 networks, prefix delegation	
Mobile Access License (Users)	100 remote SNX or Mobile VPN client users	
Hardware		
WAN Port	1x 10/100/1000Base-T RJ-45 port	
LAN Ports	5x 10/100/1000Base-T RJ-45 ports	
Wi-Fi (optional)	802.11 a/b/g/n/ac/ax MU-MIMO 3x3	
Radio Band	One radio band non-concurrent: 2.4GHz or 5GHz	
Console Port	1x USB-C	
USB Port	1x USB 3.0	
Dimensions		
Enclosure	Desktop, wall mount	
Dimensions (W x D x H)	210 x 160 x 37.5 mm, 8.3 x 6.3 x 1.5 in.	
Weight	0.43 kg (0.95 lbs.)	
Environment		
Operating / Storage	0°C ~ 40°C / -45°C ~ 60°C	C (5~95%, non-condensing)
Power Requirements		
AC Input	100 - 240VAC, 50 - 60 Hz	
Power Supply Rating	12V/3.3A 40W power adapter	
	17.92 (non-Wi-Fi); 21.95W (Wi-Fi)	
Power Consumption (Max)	17.92 (non-Wi-Fi	J; 21.95W (Wi-Fi)

<sup>1.</sup> Includes Firewall, Application Control, URL Filtering, IPS, Antivirus, Anti-Bot, SandBlast Zero-Day Protection with logging. 2. Includes Firewall, Application Control, IPS with logging.

<sup>\*</sup> Smart Accel is available on release R81.10 and above. Smart Accel must be enabled on Web UI and is currently supported on devices managed via Web UI or SM





# SAVE NOW ON SMB FIREWALLS



### **SPECIFICATIONS**

#### 1595 Pro (Wi-Fi, 5G model)

- 1 802.11 a/b/g/n/ac/ax (Wi-Fi 5G option)
- 8x 1GbE LAN switch
- 3 1x 1GbE copper/fiber DMZ port
- 4 1x 1GbE WAN port
- 6 USB 3.0 port
- 6 USB-C console port
- 12V power connector






	1575	1595	
Enterprise Testing Conditions			
Threat Prevention with Smart Accel*	650 Mbps	900 Mbps	
Threat Prevention <sup>1</sup>	500 Mbps	660 Mbps	
Next Generation Firewall <sup>2</sup>	970 Mbps	1,300 Mbps	
IPS Throughput	1,050 Mbps	1,400 Mbps	
Firewall Throughput	2,800 Mbps	2,800 Mbps	
RFC 3511, 2544, 2647, 1242 Performance (	LAB)		
Firewall 1518 Byte UDP Packets	6,400 Mbps	6,400 Mbps	
VPN AES-128 Throughput	1,950 Mbps	2,600 Mbps	
Connections per Second	15,750	21,000	
Concurrent Connections	1,000,000	1,000,000	
Software			
Security	Firewall, VPN, User Aware, QoS, Application Control, URLF, IPS, Anti-Bot, Antivirus, Anti-Spam, sandboxing		
Unicast, Multicast Routing and Clustering	OSPFv2, BGPv4 and 4++, RIP, PIM (SM, DM, SSM), IGMP, ClusterXL High Availability		
IPv6	local network and internet connections, dual stack tunneling IPv4 over IPv6 networks, prefix delegation		
Mobile Access License (Users)	200 remote SNX or Mobile VPN client users		
Hardware			
WAN Port	1x 10/100/1000Base-T RJ-45 port		
DMZ Port	1x 10/100/1000Base-T RJ-45 / 1x 1000BaseF SFP port (transceiver not included)		
LAN Ports	8x 10/100/1000Base-T RJ-45 ports		
Wi-Fi (optional)	802.11 a/b/g/n/ac/ax MU-MIMO 4x4		
Radio Band	Two radio bands concurrent: 2.4GHz and 5GHz		
5G (1595 option)	Sub-6 GHz, max 4.5Gbps downlink speed and 660Mbps uplink speed. eSIM and external SIM support. Dual SIM single standby (DSSS). 4x4 MIMO		
Console, USB ports	Console: 1x USB-C, USB1x USB 3.0:		
SD Card Slot	Micro-SD slot		
Dimensions			
Dimensions (W x D x H)	Desktop form factor: 210 x 170 x 42 mm, 8.3 x 6.7 x 1.7 in.		
Weight	0.87 kg (1.9 lbs.)		
Environment			
Operating / Storage	0°C ~ 40°C / -45°C ~ 60°C (5~95%, non-condensing)		
Power Requirements			
AC Input	100 - 240VAC, 50 - 60 Hz		
Power Supply Rating	12V/3.3A 40W power adapter (non-Wi-Fi), 12V/5A 60W power adapter (all Wi-Fi models)		
Developed (Man)		26.01W (non-Wi-Fi); 31.28W (Wi-Fi); 35.5W (Wi-Fi-LTE), 37.26W (Wi-Fi-DSL)	
Power Consumption (Max)	26.01W (non-Wi-Fi); 31.28W (Wi-Fi); 3	35.5W (Wi-Fi-LTE), 37.26W (Wi-Fi-DSL)	

<sup>1.</sup> Includes Firewall, Application Control, URL Filtering, IPS, Antivirus, Anti-Bot, SandBlast Zero-Day Protection with logging. 2. Includes Firewall, Application Control, IPS with logging.

<sup>\*</sup> Smart Accel is available on release R81.10 and above. Smart Accel must be enabled on Web UI and is currently supported on devices managed via Web UI or SMP





## What Are You Waiting For?

Security for a small business is too important to ignore. With Check Point, small businesses can feel confident that they have the best security available, in a package that does not require extensive expertise or time to get high levels of protection.

Contact your Check Point TD Synnex team at <a href="mailto:checkpointBD@tdsynnex.com">checkpointBD@tdsynnex.com</a> today !



## **About Check Point**

Check Point Software Technologies Ltd. (<a href="www.checkpoint.com">www.checkpoint.com</a>) is a leading provider of cyber security solutions globally. Its solutions protect customers from cyber-attacks with an industry leading catch rate of malware, ransomware and other types of attacks.

Check Point offers a multilevel security architecture that defends enterprises' cloud, network and mobile device held information, plus the most comprehensive and intuitive one point of control security management system. Check Point protects over 100,000 organizations of all sizes.

959 Skyway Road, Suite 300, San Carlos, CA 94070 | Tel: 1-800-429-4391 www.checkpoint.com.